

EXHIBIT 16

Electronic Acknowledgement Receipt

EFS ID:	35718901
Application Number:	16383561
International Application Number:	
Confirmation Number:	5592
Title of Invention:	Zone Scene Management
First Named Inventor/Applicant Name:	Robert A. Lambourne
Customer Number:	135176
Filer:	Brandon Jacob Kennedy
Filer Authorized By:	
Attorney Docket Number:	07-0901-CON0419A
Receipt Date:	12-APR-2019
Filing Date:	
Time Stamp:	23:31:48
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	CARD
Payment was successfully received in RAM	\$5860
RAM confirmation Number	041519INTEFSW23323300
Deposit Account	506632
Authorized User	Brandon Kennedy

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

37 CFR 1.16 (National application filing, search, and examination fees)

37 CFR 1.17 (Patent application and reexamination processing fees)

37 CFR 1.19 (Document supply fees)

37 CFR 1.20 (Post Issuance fees)

37 CFR 1.21 (Miscellaneous fees and charges)

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Authorization for Extension of Time all replies	07-0901- CON0419A_General_Authoriza tion.pdf	86167	no	1
			1f1a050900041e4c135dd3828d00d80c63e0af1c		
Warnings:					
Information:					
2	Oath or Declaration filed	13-0504_Executed_Declaration .pdf	114762	no	1
			5e60005e790c46551134ee2c4bbbddec04532e61		
Warnings:					
Information:					
3	TrackOne Request	07-0901- CON0419A_Track1Request.pdf	113890	no	2
			da09343ea4b81bf0bb8a341ef6264cc4851844d9		
Warnings:					
Information:					
4	Drawings-only black and white line drawings	07-0901-CON0419A_Figures. PDF	305231	no	11
			a1a7709e56b88d0fa0345bc04a3c2750169bd484		
Warnings:					
Information:					
5		07-0901- CON0419A_Specification.pdf	1792031	yes	30
			5af1e66bdb05a7d75f13814f9d53bcbf5bdda17d		
	Multipart Description/PDF files in .zip description				
	Document Description		Start	End	
	Specification		1	21	
	Claims		22	29	
	Abstract		30	30	

Warnings:**Information:**

6	Application Data Sheet	07-0901-CON0419A_ADS.pdf	1256416	no	9
			e51c63462f7adf6bcac12582167b5a36b328c7ab		

Warnings:**Information:**

7	Power of Attorney	07-0901-CON0419A_POA.pdf	254834	no	2
			e4c0f104f304e889e4cdab0c595f4bf09f7c8858		

Warnings:**Information:**

8	Fee Worksheet (SB06)	fee-info.pdf	40285	no	2
			12aba03191cadf8880a97fa534d5e727cb61aa9c		

Warnings:**Information:**

Total Files Size (in bytes):			3963616
-------------------------------------	--	--	---------

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

**Application for a United States Patent United
States Patent and Trademark Office**

Title: Zone Scene Management

Inventor(s): Robert A. Lambourne

Assignee: Sonos, Inc.
614 Chapala St.
Santa Barbara, CA 93101

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of and claims priority to U.S. Patent Application Serial No. 15/130,919, filed on April 15, 2016, entitled "ZONE SCENE ACTIVATION," which is a continuation of U.S. Patent Application Serial No. 14/465,457, filed on August 21, 2014, entitled "METHOD AND APPARATUS FOR UPDATING ZONE CONFIGURATIONS IN A MULTI-ZONE SYSTEM," which is a continuation of U.S. Patent Application Serial No. 13/896,829, filed on May 17, 2013, entitled "METHOD AND APPARATUS FOR UPDATING ZONE CONFIGURATIONS IN A MULTI-ZONE SYSTEM," which is a continuation of U.S. Patent Application Serial No. 11/853,790, filed September 11, 2007, entitled "CONTROLLING AND MANIPULATING GROUPINGS IN A MULTI-ZONE MEDIA SYSTEM," which claims priority to U.S. Provisional Application No. 60/825,407 filed on September 12, 2006, entitled "CONTROLLING AND MANIPULATING GROUPINGS IN A MULTI-ZONE MEDIA SYSTEM," each of which is hereby incorporated by reference in its entirety for all purposes.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The invention is generally related to the area of consumer electronics and human-computer interaction. In particular, the invention is related to method and apparatus for controlling or manipulating a plurality of multimedia players in a multi-zone system.

[0003] An enduring passion for quality audio reproduction or system is continuing to drive demands from users. One of the demands includes an audio system in a house in which, for example, one could grill to classic rock on a patio while another one may cook up his/her own music selections in a kitchen. This is all at the same time while a teenager catches a ballgame in a family room, and another one blasts pop in a bedroom. And the best part of such audio system is that each family member does not need his or her own stereo system - one system gives everyone access to all the music sources.

[0004] Currently, one of the systems that can meet part of such demand is a conventional multi-zone audio system that usually includes a number of audio players. Each of the audio players has its own amplifier(s) and a set of speakers and typically installed in one place (e.g., a room). In order to play an audio source at one location, the audio source must be provided locally or from a centralized location. When the audio source is provided locally, the multi-zone audio system functions as a collection of many stereo systems, making source sharing difficult. When the audio source is provided centrally, the centralized location may include a juke box, many compact discs, an AM or FM radio, tapes, or others. To send an audio source to an audio player demanding such source, a cross-bar type of device is used to prevent the audio source from going to other audio players that may be playing other audio sources.

[0005] In order to achieve playing different audio sources in different audio players, the traditional multi-zone audio system is generally either hard-wired or controlled by a pre-configured and pre-programmed controller. While the pre-programmed configuration may be satisfactory in one situation, it may not be suitable for another situation. For example, a person would like to listen to broadcast news from his/her favorite radio station in a bedroom, a bathroom and a den while preparing to go to work in the morning. The same person may wish to listen in the den and the living room to music from a compact disc in the evening. In order to satisfy such requirements, two groups of audio players must be established. In the morning, the audio players in the bedroom, the bathroom and the den need to be grouped for the broadcast news. In the evening, the audio players in the den and the living room are grouped for the music. Over the weekend, the audio players in the den, the living room, and a kitchen are grouped for party music. Because the morning group, the evening group and the weekend group contain the den, it can be difficult for the traditional

system to accommodate the requirement of dynamically managing the ad hoc creation and deletion of groups.

[0006] There is a need for dynamic control of the audio players as a group. With a minimum manipulation, the audio players may be readily grouped. In a traditional multi-zone audio system, the audio players have to be adjusted one at a time, resulting in an inconvenient and non-homogenous audio environment. Further, there is a need to individually or systematically adjust the audio volume of the audio players.

SUMMARY OF THE INVENTION

[0007] This section is for the purpose of summarizing some aspects of the present invention and to briefly introduce some preferred embodiments. Simplifications or omissions in this section as well as in the abstract or the title of this description may be made to avoid obscuring the purpose of this section, the abstract and the title. Such simplifications or omissions are not intended to limit the scope of the present invention.

[0008] In general, the present invention pertains to controlling a plurality of multimedia players, or simply players, in groups. According to one aspect of the present invention, a mechanism is provided to allow a user to group some of the players according to a theme or scene, where each of the players is located in a zone. When the scene is activated, the players in the scene react in a synchronized manner. For example, the players in the scene are all caused to play an audio source or music in a playlist, wherein the audio source may be located anywhere on a network.

[0009] According to another aspect of the present invention, the scene may be activated at any time or a specific time. A user may activate the scene at any time so that only some selected zones in an entertainment system facilitate a playback of an

audio source. When the scene is activated at a specific time, the scene may be used as an alarm or buzzer.

[0010] According to still another aspect of the present invention, a controlling device (also referred to herein as controller) is provided to facilitate a user to select any of the players in the system to form respective groups each of which is set up per a scene. Although various scenes may be saved in any of the members in a group, commands are preferably sent from the controller to the rest of the members when one of the scenes is executed. Depending on implementation, the commands include parameters pertaining to identifiers of the players, volumes settings, audio source and etc.

[0011] According to yet another aspect of the present invention, a configurable module is implemented in the controlling device that provides interactive graphic user interface for forming, managing and controlling groups in the system, de-grouping a group or adjusting audio volume of individual players or a group of players.

[0012] The present invention may be implemented in many forms including software, hardware or a combination of both. According to one embodiment, the present invention is directed to a method for groupings in a multi-zone media system, the method comprises providing a mechanism to allow a user to determine which players in the system to be associated with a theme representing a group; and configuring the theme with parameters pertaining to the players, wherein the theme is activated at anytime or a specific time so that the players react in a synchronized manner. The players in a scene are synchronized to play a multimedia file when the scene is activated.

[0013] According to another embodiment, the present invention is directed to an entertainment system for grouping players, the system comprises: a plurality of players,

each located in one zone; and a controller providing a mechanism to allow a user to select which of the players to be associated with a theme representing a group; and configure the theme with parameters pertaining to the selected players, wherein the theme is activated at anytime or a specific time so that the selected players react in a synchronized manner. As a result, the selected players are synchronized to play a multimedia that is in a digital format and retrieved from a source over a network.

[0014] One of the objects, features, and advantages of the present invention is to remotely control a plurality of multimedia players in a multi-zone system, playing and controlling the audio source synchronously if the players are grouped together, or playing and controlling the audio source individually if the players are disassociated with each other.

[0015] Other objects, features, and advantages of the present invention will become apparent upon examining the following detailed description of an embodiment thereof, taken in conjunction with the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] These and other features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings where:

[0017] FIG. 1 shows an exemplary configuration in which the present invention may be practiced;

[0018] FIG. 2A shows an exemplary functional block diagram of a player in accordance with the present invention;

[0019] FIG. 2B shows an example of a controller that may be used to remotely control one of more players of FIG. 2A;

[0020] FIG. 2C shows an exemplary internal functional block diagram of a controller in accordance with one embodiment of the present invention;

[0021] FIG. 3A provides an illustration of one zone scene, where the left column shows the starting zone grouping – all zones are separate, the column on the right shows the effects of grouping the zones to make a group of 3 zones named after “Morning”;

[0022] FIG. 3B shows that a user defines multiple groups to be gathered at the same time;

[0023] FIG. 4 shows an exemplary user interface that may be displayed on a controller or a computer of FIG. 1;

[0024] FIG. 5A shows a user interface to allow a user to form a scene;

[0025] FIG. 5B shows another user interface **520** to allow a user to form a scene;

[0026] FIG. 5C shows a user interface to allow a user to adjust a volume level of the zone players in a zone scene individually or collectively; and

[0027] FIG. 6 shows a flowchart or process of providing a player theme or a zone scene for a plurality of players, where one or more of the players are placed in a zone.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0028] The detailed description of the invention is presented largely in terms of procedures in terms of procedures, steps, logic blocks, processing, and other symbolic

representations that directly or indirectly resemble the operations of data processing devices coupled to networks. These process descriptions and representations are typically used by those skilled in the art to most effectively convey the substance of their work to others skilled in the art. Numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will become obvious to those skilled in the art that the present invention may be practiced without these specific details. In other instances, well known methods, procedures, components, and circuitry have not been described in detail to avoid unnecessarily obscuring aspects of the present invention.

[0029] Reference herein to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment can be included in at least one embodiment of the invention. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. Further, the order of blocks in process flowcharts or diagrams representing one or more embodiments of the invention do not inherently indicate any particular order nor imply any limitations in the invention.

[0030] Referring now to the drawings, in which like numerals refer to like parts throughout the several views. FIG. 1 shows an exemplary configuration **100** in which the present invention may be practiced. The configuration may represent, but not be limited to, a part of a residential home, a business building or a complex with multiple zones. There are a number of multimedia players of which three examples **102**, **104** and **106** are shown as audio devices. Each of the audio devices may be installed or provided in one particular area or zone and hence referred to as a zone player herein.

[0031] As used herein, unless explicitly stated otherwise, an audio source or audio sources are in digital format and can be transported or streamed over a data network. To facilitate the understanding of the present invention, it is assumed that the configuration **100** represents a home. Thus, the zone player **102** and **104** may be located in two of the bedrooms respectively while the zone player **106** may be installed in a living room. All of the zone players **102**, **104** and **106** are coupled directly or indirectly to a data network **108**. In addition, a computing device **110** is shown to be coupled on the network **108**. In reality, any other devices such as a home gateway device, a storage device, or an MP3 player may be coupled to the network **108** as well.

[0032] The network **108** may be a wired network, a wireless network or a combination of both. In one example, all devices including the zone players **102**, **104** and **106** are coupled to the network **108** by wireless means based on an industry standard such as IEEE 802.11. In yet another example, all devices including the zone players **102**, **104** and **106** are part of a local area network that communicates with a wide area network (e.g., the Internet).

[0033] Many devices on the network **108** are configured to download and store audio sources. For example, the computing device **110** can download audio sources from the Internet and store the downloaded sources locally for sharing with other devices on the Internet or the network **108**. The computing device **110** or any of the zone players can also be configured to receive streaming audio. Shown as a stereo system, the device **112** is configured to receive an analog audio source (e.g., from broadcasting) or retrieve a digital audio source (e.g., from a compact disk). The analog audio sources can be converted to digital audio sources. In accordance with the present invention, the audio source may be shared among the devices on the network **108**.

[0034] Two or more zone players may be grouped together to form a new zone group. Any combinations of zone players and an existing zone group may be grouped together. In one instance, a new zone group is formed by adding one zone player to another zone player or an existing zone group.

[0035] Referring now to FIG. 2A, there is shown an exemplary functional block diagram of a zone player **200** in accordance with the present invention. The zone player **200** includes a network interface **202**, a processor **204**, a memory **206**, an audio processing circuit **210**, a module **212**, and optionally, an audio amplifier **214** that may be internal or external. The network interface **202** facilitates a data flow between a data network (i.e., the data network **108** of FIG. 1) and the zone player **200** and typically executes a special set of rules (i.e., a protocol) to send data back and forth. One of the common protocols used in the Internet is TCP/IP (Transmission Control Protocol/Internet Protocol). In general, a network interface manages the assembling of an audio source or file into smaller packets that are transmitted over the data network or reassembles received packets into the original source or file. In addition, the network interface **202** handles the address part of each packet so that it gets to the right destination or intercepts packets destined for the zone player **200**.

[0036] The network interface **202** may include one or both of a wireless interface **216** and a wired interface **217**. The wireless interface **216**, also referred to as a RF interface, provides network interface functions by a wireless means for the zone player **200** to communicate with other devices in accordance with a communication protocol (such as the wireless standard IEEE 802.11a, 802.11b or 802.11g). The wired interface **217** provides network interface functions by a wired means (e.g., an Ethernet cable). In one embodiment, a zone player includes both of the interfaces **216** and **217**, and other zone players include only a RF or wired interface. Thus these other zone players communicate with other devices on a network or retrieve audio sources via the zone

player. The processor **204** is configured to control the operation of other parts in the zone player **200**. The memory **206** may be loaded with one or more software modules that can be executed by the processor **204** to achieve desired tasks. According to one aspect of the present invention, a software module implementing one embodiment of the present invention is executed, the processor **204** operates in accordance with the software module in reference to a saved zone group configuration characterizing a zone group created by a user, the zone player **200** is caused to retrieve an audio source from another zone player or a device on the network.

[0037] According to one embodiment of the present invention, the memory **206** is used to save one or more saved zone configuration files that may be retrieved for modification at any time. Typically, a saved zone group configuration file is transmitted to a controller (e.g., the controlling device **140** or **142** of FIG. 1, a computer, a portable device, or a TV) when a user operates the controlling device. The zone group configuration provides an interactive user interface so that various manipulations or control of the zone players may be performed.

[0038] The audio processing circuit **210** resembles most of the circuitry in an audio playback device and includes one or more digital-to-analog converters (DAC), an audio preprocessing part, an audio enhancement part or a digital signal processor and others. In operation, when an audio source is retrieved via the network interface **202**, the audio source is processed in the audio processing circuit **210** to produce analog audio signals. The processed analog audio signals are then provided to the audio amplifier **214** for playback on speakers. In addition, the audio processing circuit **210** may include necessary circuitry to process analog signals as inputs to produce digital signals for sharing with other devices on a network.

[0039] Depending on an exact implementation, the module **212** may be implemented as a combination of hardware and software. In one embodiment, the module **212** is used to save a scene. The audio amplifier **214** is typically an analog circuit that powers the provided analog audio signals to drive one or more speakers.

[0040] Referring now to FIG. 2B, there is shown an exemplary controller **240**, which may correspond to the controlling device **140** or **142** of FIG. 1. The controller **240** may be used to facilitate the control of multi-media applications, automation and others in a complex. In particular, the controller **240** is configured to facilitate a selection of a plurality of audio sources available on the network, controlling operations of one or more zone players (e.g., the zone player **200**) through a RF interface corresponding to the RF interface **216** of FIG. 2A. According to one embodiment, the wireless means is based on an industry standard (e.g., infrared, radio, wireless standard IEEE 802.11a, 802.11b or 802.11g). When a particular audio source is being played in the zone player **200**, a picture, if there is any, associated with the audio source may be transmitted from the zone player **200** to the controller **240** for display. In one embodiment, the controller **240** is used to synchronize more than one zone players by grouping the zone players in a group. In another embodiment, the controller **240** is used to control the volume of each of the zone players in a zone group individually or together.

[0041] The user interface for the controller **240** includes a screen **242** (e.g., a LCD screen) and a set of functional buttons as follows: a “zones” button **244**, a “back” button **246**, a “music” button **248**, a scroll wheel **250**, “ok” button **252**, a set of transport control buttons **254**, a mute button **262**, a volume up/down button **264**, a set of soft buttons **266** corresponding to the labels **268** displayed on the screen **242**.

[0042] The screen **242** displays various screen menus in response to a user’s selection. In one embodiment, the “zones” button **244** activates a zone management

screen or “Zone Menu”, which is described in more details below. The “back” button **246** may lead to different actions depending on the current screen. In one embodiment, the “back” button triggers the current screen display to go back to a previous one. In another embodiment, the “back” button negates the user’s erroneous selection. The “music” button **248** activates a music menu, which allows the selection of an audio source (e.g., a song) to be added to a zone player’s music queue for playback.

[0043] The scroll wheel **250** is used for selecting an item within a list, whenever a list is presented on the screen **242**. When the items in the list are too many to be accommodated in one screen display, a scroll indicator such as a scroll bar or a scroll arrow is displayed beside the list. When the scroll indicator is displayed, a user may rotate the scroll wheel **250** to either choose a displayed item or display a hidden item in the list. The “ok” button **252** is used to confirm the user selection on the screen **242**.

[0044] There are three transport buttons **254**, which are used to control the effect of the currently playing song. For example, the functions of the transport buttons may include play/pause and forward/rewind a song, move forward to a next song track, or move backward to a previous track. According to one embodiment, pressing one of the volume control buttons such as the mute button **262** or the volume up/down button **264** activates a volume panel. In addition, there are three soft buttons **266** that can be activated in accordance with the labels **268** on the screen **242**. It can be understood that, in a multi-zone system, there may be multiple audio sources being played respectively in more than one zone players. The music transport functions described herein shall apply selectively to one of the sources when a corresponding one of the zone players or zone groups is selected.

[0045] FIG. 2C illustrates an internal functional block diagram of an exemplary controller **270**, which may correspond to the controller **240** of FIG. 2B. The screen **272**

on the controller **270** may be a LCD screen. The screen **272** communicates with and is commanded by a screen driver **274** that is controlled by a microcontroller (e.g., a processor) **276**. The memory **282** may be loaded with one or more application modules **284** that can be executed by the microcontroller **276** with or without a user input via the user interface **278** to achieve desired tasks. In one embodiment, an application module is configured to facilitate grouping a number of selected zone players into a zone group and synchronizing the zone players for one audio source. In another embodiment, an application module is configured to control together the audio volumes of the zone players in a zone group. In operation, when the microcontroller **276** executes one of the application modules **284**, the screen driver **274** generates control signals to drive the screen **272** to display an application specific user interface accordingly, more of which will be described below.

[0046] The controller **270** includes a network interface **280** referred to as a RF interface **280** that facilitates wireless communication with a zone player via a corresponding RF interface thereof. In one embodiment, the commands such as volume control and audio playback synchronization are sent via the RF interfaces. In another embodiment, a saved zone group configuration is transmitted between a zone player and a controller via the RF interfaces. The controller **270** may control one or more zone players, such as **102**, **104** and **106** of FIG. 1. Nevertheless, there may be more than one controllers, each preferably in a zone (e.g., a room) and configured to control any one and all of the zone players.

[0047] In one embodiment, a user creates a zone group including at least two zone players from the controller **240** that sends signals or data to one of the zone players. As all the zone players are coupled on a network, the received signals in one zone player can cause other zone players in the group to be synchronized so that all the zone players in the group playback an identical audio source or a list of identical audio

sources in a timely synchronized manner. Similarly, when a user increases the audio volume of the group from the controller, the signals or data of increasing the audio volume for the group are sent to one of the zone players and causes other zone players in the group to be increased together in volume and in scale.

[0048] According to one implementation, an application module is loaded in memory **282** for zone group management. When a predetermined key (e.g. the “zones” button **244**) is activated on the controller **240**, the application module is executed in the microcontroller **276**. The input interface **278** coupled to and controlled by the microcontroller **276** receives inputs from a user. A “Zone Menu” is then displayed on the screen **272**. The user may start grouping zone players into a zone group by activating a “Link Zones” or “Add Zone” soft button, or de-grouping a zone group by activating an “Unlink Zones” or “Drop Zone” button. The detail of the zone group manipulation will be further discussed below.

[0049] As described above, the input interface **278** includes a number of function buttons as well as a screen graphical user interface. It should be pointed out that the controller **240** in FIG. 2B is not the only controlling device that may practice the present invention. Other devices that provide the equivalent control functions (e.g., a computing device, a hand-held device) may also be configured to practice the present invention. In the above description, unless otherwise specifically described, it is clear that keys or buttons are generally referred to as either the physical buttons or soft buttons, enabling a user to enter a command or data.

[0050] One mechanism for ‘joining’ zone players together for music playback is to link a number of zone players together to form a group. To link a number of zone players together, a user may manually link each zone player or room one after the other. For example, there is a multi-zone system that includes the following zones.

Bathroom

Bedroom

Den

Dining Room

Family Room

Foyer

[0051] If the user wishes to link 5 of the 6 zone players using the current mechanism, he/she must start with a single zone and then manually link each zone to that zone. This mechanism may be sometimes quite time consuming. According to one embodiment, a set of zones can be dynamically linked together using one command. Using what is referred to herein as a theme or a zone scene, zones can be configured in a particular scene (e.g., morning, afternoon, or garden), where a predefined zone grouping and setting of attributes for the grouping are automatically effectuated.

[0052] For instance, a “Morning” zone scene/configuration command would link the Bedroom, Den and Dining Room together in one action. Without this single command, the user would need to manually and individually link each zone. FIG. 3A provides an illustration of one zone scene, where the left column shows the starting zone grouping – all zones are separate, the column on the right shows the effects of grouping the zones to make a group of 3 zones named after “Morning”.

[0053] Expanding this idea further, a Zone Scene can be set to create multiple sets of linked zones. For example, a scene creates 3 separate groups of zones, the downstairs zones would be linked together, the upstairs zones would be linked together in their own group, and the outside zones (in this case the patio) would move into a group of its own.

[0054] In one embodiment as shown in FIG. 3B, a user defines multiple groups to be gathered at the same time. For example: an “Evening Scene” is desired to link the following zones:

- Group1
 - Bedroom
 - Den
 - Dining Room
- Group 2
 - Garage
 - Garden

where Bathroom, Family Room and Foyer should be separated from any group if they were part of a group before the Zone Scene was invoked.

[0055] One important of the features, benefits and objects in the present invention is that that zones do not need to be separated before a zone scene is invoked. In one embodiment, a command is provided and links all zones in one step, if invoked. The command is in a form of a zone scene. After linking the appropriate zones, a zone scene command could apply the following attributes:

Set volumes levels in each zones (each zone can have a different volume)

Mute/Unmute zones.

Select and play specific music in the zones.

Set the play mode of the music (Shuffle, Repeat, Shuffle-repeat)

Set the music playback equalization of each zone (e.g., bass treble).

[0056] A further extension of this embodiment is to trigger a zone scene command as an alarm clock function. For instance the zone scene is set to apply at 8:00am. It could link appropriate zones automatically, set specific music to play and

then stop the music after a defined duration. Although a single zone may be assigned to an alarm, a scene set as an alarm clock provides a synchronized alarm, allowing any zones linked in the scene to play a predefined audio (e.g., a favorable song, a predefined playlist) at a specific time or for a specific duration. If, for any reason, the scheduled music failed to be played (e.g., an empty playlist, no connection to a share, failed UPnP, no Internet connection for an Internet Radio station), a backup buzzer will sound. This buzzer will be a sound file that is stored in a zone player.

[0057] FIG. 4 shows an exemplary user interface **400** that may be displayed on a controller **142** or a computer **110** of FIG. 1. The interface **400** shows a list of items that may be set up by a user to cause a scene to function at a specific time. In the embodiment shown in FIG. 4, the list of items includes “Alarm”, “Time”, “Zone”, “Music”, “Frequency” and “Alarm length”. “Alarm” can be set on or off. When “Alarm” is set on, “Time” is a specific time to set off the alarm. “Zone” shows which zone players are being set to play a specified audio at the specific time. “Music” shows what to be played when the specific time arrives. “Frequency” allows the user to define a frequency of the alarm. “Alarm length” defines how long the audio is to be played. It should be noted that the user interface **400** is provided herein to show some of the functions associated with setting up an alarm. Depending on an exact implementation, other functions, such as time zone, daylight savings, time synchronization, and time/date format for display may also be provided without departing from the present invention.

[0058] According to one embodiment, each zone player in a scene may be set up for different alarms. For example, a “Morning” scene includes three zone players, each in a bedroom, a den, and a dining room. After selecting the scene, the user may set up an alarm for the scene as whole. As a result, each of the zone players will be activated at a specific time.

[0059] FIG. 5A shows a user interface **500** to allow a user to form a scene. The panel on the left shows the available zones in a household. The panel on the right shows the zones that have been selected and be grouped as part of this scene. Depending on an exact implementation of a user interface, Add/Remove buttons may be provided to move zones between the panels, or zones may be dragged along between panels.

[0060] FIG. 5B shows another user interface **520** to allow a user to form a scene. The user interface **520** that may be displayed on a controller or a computing device, lists available zones in a system. A checkbox is provide next to each of the zones so that a user may check in the zones to be associated with the scene.

[0061] FIG. 5C shows a user interface **510** to allow a user to adjust a volume level of the zone players in a zone scene individually or collectively. As shown in the user interface **510**, the 'Volumes...' button (shown as sliders, other forms are possible) allows the user to affect the volumes of the associated zone players when a zone scene is invoked. In one embodiment, the zone players can be set to retain whatever volume that they currently have when the scene is invoked. Additionally the user can decide if the volumes should be unmuted or muted when the scene is invoked.

[0062] FIG. 6 shows a flowchart or process **600** of providing a player theme or a zone scene for a plurality of players, where one or more of the players are placed in a zone. The process **600** is presented in accordance with one embodiment of the present invention and may be implemented in a module to be located in the memory **282** of FIG. 2C.

[0063] The process **600** is initiated only when a user decides to proceed with a zone scene at **602**. The process **600** then moves to **604** where it allows a user to decide which zone players to be associated with the scene. For example, there are ten players

in a household, and the scene is named after “Morning”. The user may be given an interface to select four of the ten players to be associated with the scene. At **606**, the scene is saved. The scene may be saved in any one of the members in the scene. In the example of FIG. 1, the scene is saved in one of the zone players and displayed on the controller **142**. In operation, a set of data pertaining to the scene includes a plurality of parameters. In one embodiment, the parameters include, but may not be limited to, identifiers (e.g., IP address) of the associated players and a playlist. The parameters may also include volume/tone settings for the associated players in the scene. The user may go back to **602** to configure another scene if desired.

[0064] Given a saved scene, a user may activate the scene at any time or set up a timer to activate the scene at **610**. The process **600** can continue when a saved scene is activated at **610**. At **612**, upon the activation of a saved scene, the process **600** checks the status of the players associated with the scene. The status of the players means that each of the players shall be in condition to react in a synchronized manner. In one embodiment, the interconnections of the players are checked to make sure that the players communicate among themselves and/or with a controller if there is such a controller in the scene.

[0065] It is assumed that all players associated with the scene are in good condition. At **614**, commands are executed with the parameters (e.g., pertaining to a playlist and volumes). In one embodiment, data including the parameters is transported from a member (e.g., a controller) to other members in the scene so that the players are caused to synchronize an operation configured in the scene. The operation may cause all players to play back a song in identical or different volumes or to play back a pre-stored file.

[0066] One of the features, benefits and advantages in the present invention is to allow sets of related devices (controllers and operating components) to exist as a group without interfering with other components that are potentially visible on the same wired or wireless network. Each of the sets is configured to a theme or a scene.

[0067] The present invention has been described in sufficient detail with a certain degree of particularity. It is understood to those skilled in the art that the present disclosure of embodiments has been made by way of examples only and that numerous changes in the arrangement and combination of parts may be resorted to without departing from the spirit and scope of the invention as claimed. While the embodiments discussed herein may appear to include some limitations as to the presentation of the information units, in terms of the format and arrangement, the invention has applicability well beyond such embodiment, which can be appreciated by those skilled in the art. Accordingly, the scope of the present invention is defined by the appended claims rather than the foregoing description of embodiments.

CLAIMS

I Claim:

1. A playback device comprising:

one or more processors;

a non-transitory computer-readable medium; and

program instructions stored on the non-transitory computer-readable medium that, when executed by the one or more processors, cause the playback device to perform functions comprising:

while operating in a first zone of a media playback system, receiving, from a network device over a data network, a first indication that the first zone has been added to a first zone scene comprising a first preconfigured grouping of zones including at least the first zone and a second zone that are to be configured for synchronous playback of media when the first zone scene is invoked;

receiving, from the network device over the data network, a second indication that the first zone has been added to a second zone scene comprising a second preconfigured grouping of zones including at least the first zone and a third zone that are to be configured for synchronous playback of media when the second zone scene is invoked, wherein the second zone is different than the third zone;

after a given one of the first and second zone scenes has been selected for invocation, receiving, from the network device over the data network, an instruction to operate in accordance with the given one of the first and second zone scenes; and

based on the instruction, beginning to operate in accordance with the given one of the first and second zone scenes such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the media playback system.

2. The playback device of claim 1, wherein the instruction to operate in accordance with the

given one of the first and second zone scenes comprises an instruction to operate in accordance with the first zone scene, and wherein beginning to operate in accordance with the given one of the first and second zone scenes comprises beginning to operate in accordance with the first zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices of the second zone.

3. The playback device of claim 2, wherein the instruction is a first instruction, and wherein the playback device further comprises program instructions stored on the non-transitory computer-readable medium that, when executed by the one or more processors, cause the playback device to perform functions comprising:

while operating in accordance with the first zone scene, receiving, from the network device over the data network, a second instruction to operate in accordance with the second zone scene; and

based on the second instruction, (a) ceasing to operate in accordance with the first zone scene such that the playback device is no longer configured to play back audio in synchrony the one or more other playback devices in the second zone and (b) beginning to operate in accordance with the second zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the third zone.

4. The playback device of claim 2, wherein the first zone scene further comprises an indication of predetermined media to be played when the first zone scene is invoked, and wherein the playback device further comprises program instructions stored on the non-transitory computer-readable medium that, when executed by the one or more processors, cause the playback device to perform functions comprising:

based on the instruction, playing back the predetermined media in synchrony with the one or more other playback devices in the second zone.

5. The playback device of claim 1, wherein the instruction to operate in accordance with the given one of the first and second zone scenes comprises an instruction to operate in accordance with the second zone scene, and wherein beginning to operate in accordance with the given one of the first and second zone scenes comprises beginning to operate in accordance with the second zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the third zone.

6. The playback device of claim 5, wherein the instruction is a first instruction, and wherein the playback device further comprises program instructions stored on the non-transitory computer-readable medium that, when executed by the one or more processors, cause the playback device to perform functions comprising:

while operating in accordance with the second zone scene, receiving, from the network device over the data network, a second instruction to operate in accordance with the first zone scene; and

based on the second instruction, (a) ceasing to operate in accordance with the second zone scene such that the playback device is no longer configured to play back audio in synchrony the one or more other playback devices in the third zone and (b) beginning to operate in accordance with the first zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the second zone.

7. The playback device of claim 1, wherein the first preconfigured grouping of zones does not include the third zone, and wherein the second preconfigured grouping of zones does not include the second zone.

8. A non-transitory computer-readable medium, wherein the non-transitory computer-readable

medium is provisioned with program instructions that are executable to cause a playback device to perform functions comprising:

while operating in a first zone of a media playback system, receiving, from a network device over a data network, a first indication that the first zone has been added to a first zone scene comprising a first preconfigured grouping of zones including at least the first zone and a second zone that are to be configured for synchronous playback of media when the first zone scene is invoked;

receiving, from the network device over the data network, a second indication that the first zone has been added to a second zone scene comprising a second preconfigured grouping of zones including at least the first zone and a third zone that are to be configured for synchronous playback of media when the second zone scene is invoked, wherein the second zone is different than the third zone;

after a given one of the first and second zone scenes has been selected for invocation, receiving, from the network device over the data network, an instruction to operate in accordance with the given one of the first and second zone scenes; and

based on the instruction, beginning to operate in accordance with the given one of the first and second zone scenes such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the media playback system.

9. The non-transitory computer-readable medium of claim 8, wherein the instruction to operate in accordance with the given one of the first and second zone scenes comprises an instruction to operate in accordance with the first zone scene, and wherein beginning to operate in accordance with the given one of the first and second zone scenes comprises beginning to operate in accordance with the first zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the second zone.

10. The non-transitory computer-readable medium of claim 9, wherein the instruction is a first instruction, and wherein the non-transitory computer-readable medium is also provisioned with program instructions that, when executed by the one or more processors, cause the playback device to perform functions comprising:

while operating in accordance with the first zone scene, receiving, from the network device over the data network, a second instruction to operate in accordance with the second zone scene; and

based on the second instruction, (a) ceasing to operate in accordance with the first zone scene such that the playback device is no longer configured to play back audio in synchrony the one or more other playback devices in the second zone and (b) beginning to operate in accordance with the second zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the third zone.

11. The non-transitory computer-readable medium of claim 9, wherein the first zone scene further comprises an indication of predetermined media to be played when the first zone scene is invoked, and wherein the non-transitory computer-readable medium is also provisioned with program instructions that, when executed by the one or more processors, cause the playback device to perform functions comprising:

based on the instruction, playing back the predetermined media in synchrony with the one or more other playback devices in the second zone.

12. The playback device of claim 8, wherein the instruction to operate in accordance with the given one of the first and second zone scenes comprises an instruction to operate in accordance with the second zone scene, and wherein beginning to operate in accordance with the given one of the first and second zone scenes comprises beginning to operate in accordance with the second zone scene such that the playback device is configured to play back audio in synchrony

with one or more other playback devices in the third zone.

13. The playback device of claim 12, wherein the instruction is a first instruction, and wherein the non-transitory computer-readable medium is also provisioned with program instructions that, when executed by the one or more processors, cause the playback device to perform functions comprising:

while operating in accordance with the second zone scene, receiving, from the network device over the data network, a second instruction to operate in accordance with the first zone scene; and

based on the second instruction, (a) ceasing to operate in accordance with the second zone scene such that the playback device is no longer configured to play back audio in synchrony with the one or more other playback devices in the third zone and (b) beginning to operate in accordance with the first zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the second zone.

14. The playback device of claim 8, wherein the first preconfigured grouping of zones does not include the third zone, and wherein the second preconfigured grouping of zones does not include the second zone.

15. A method executed by a playback device, the method comprising:

while operating in a first zone of a media playback system, receiving, from a network device over a data network, a first indication that the first zone has been added to a first zone scene comprising a first preconfigured grouping of zones including at least the first zone and a second zone that are to be configured for synchronous playback of media when the first zone scene is invoked;

receiving, from the network device over the data network, a second indication that the first

zone has been added to a second zone scene comprising a second preconfigured grouping of zones including at least the first zone and a third zone that are to be configured for synchronous playback of media when the second zone scene is invoked, wherein the second zone is different than the third zone;

after a given one of the first and second zone scenes has been selected for invocation, receiving, from the network device over the data network, an instruction to operate in accordance with the given one of the first and second zone scenes; and

based on the instruction, beginning to operate in accordance with the given one of the first and second zone scenes such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the media playback system.

16. The method of claim 15, wherein the instruction to operate in accordance with the given one of the first and second zone scenes comprises an instruction to operate in accordance with the first zone scene, and wherein beginning to operate in accordance with the given one of the first and second zone scenes comprises beginning to operate in accordance with the first zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the second zone.

17. The method of claim 16, wherein the instruction is a first instruction, the method further comprising:

while operating in accordance with the first zone scene, receiving, from the network device over the data network, a second instruction to operate in accordance with the second zone scene; and

based on the second instruction, (a) ceasing to operate in accordance with the first zone scene such that the playback device is no longer configured to play back audio in synchrony the one or more other playback devices in the second zone and (b) beginning to operate in

accordance with the second zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the third zone.

18. The method of claim 16, wherein the first zone scene further comprises an indication of predetermined media to be played when the first zone scene is invoked, the method further comprising:

based on the instruction, playing back the predetermined media in synchrony with the one or more other playback devices in the second zone.

19. The method of claim 15, wherein the instruction to operate in accordance with the given one of the first and second zone scenes comprises an instruction to operate in accordance with the second zone scene, and wherein beginning to operate in accordance with the given one of the first and second zone scenes comprises beginning to operate in accordance with the second zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the third zone.


20. The method of claim 19, wherein the instruction is a first instruction, the method further comprising:


while operating in accordance with the second zone scene, receiving, from the network device over the data network, a second instruction to operate in accordance with the first zone scene; and


based on the second instruction, (a) ceasing to operate in accordance with the second zone scene such that the playback device is no longer configured to play back audio in synchrony with the one or more other playback devices in the third zone and (b) beginning to operate in accordance with the first zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the second zone.

ABSTRACT

An example playback device in a first zone of a media playback system receives a first indication that the first zone has been added to a first zone scene including a first preconfigured grouping of zones including the first zone and a second zone. The playback device receives a second indication that the first zone has been added to a second zone scene including a second preconfigured grouping of zones including the first zone and a third zone. After a given one of the first and second zone scenes has been selected for invocation, the playback device receives an instruction to operate in accordance with the given zone scene, and based on the instruction, begins operating in accordance with the given zone scene such that the playback device is configured to play back audio in synchrony with one or more other playback devices in the media playback system.







270




FIG. 2C




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5A





FIG. 5B



510

FIG. 5C




FIG. 6